NERA






La lampada da parete per esterni NERA combina l'eleganza contemporanea con un design minimalista e distintivo, offrendo una soluzione illuminotecnica sofisticata per gli spazi esterni moderni. Il suo aspetto raffinato valorizza i dettagli architettonici, aggiungendo un tocco accogliente a ingressi, balconi, terrazze, muri da giardino, vialetti e facciate degli edifici. Ideale per ambienti residenziali, commerciali e ricettivi, NERA si integra armoniosamente con diversi stili architettonici, unendo eleganza e funzionalità nei progetti di illuminazione per esterni.

The NERA Outdoor Wall Light combines contemporary elegance with a distinctive, minimalist design, creating a sophisticated lighting solution for modern exterior spaces. Its refined appearance enhances architectural features while adding a welcoming touch to entrances, balconies, terraces, garden walls, pathways, and building facades. Suitable for residential, commercial, and hospitality environments, NERA complements a variety of architectural styles, bringing elegance and functionality to outdoor lighting projects.

Description





Housing - High-grade aluminium construction with tiger powder spraying surface teatment. engineered for superior outdoor durability and corrosion resistance.
Diffuser - High-transmittance optical diffuser with a precision-angled reflector for glare-free distribution.
Reflector - Precision beam control (120°).
LED - sustainable energy savings enabled by advanced LED technogy (Efficiency: 100Lm/W , UGR<19).
L80 / B10 @ 50,000 h (LM-80 / TM-21)
L70 / B15 @ 100,000 h (projected lifetime under typical conditions)
Failure rate: F10 @ 50,000 h , Ta 25 - 40°C
Standards - Manufactured in accordance with tested as per PTPS IES62722 , Glowing Wire Test 850°.

Model	Power	Illuminance	Size(mm)
NERA 12 A	12W	1200Lm	170mm×H250mm
NERA 12 B	12W	1200Lm	210mm×H210mm

- 6500 K
- 6000 K
- 5000 K
- 4000 K
- 3000 K
- 2700 K

k





CREE SHARP SAMSUNG PHILIPS CITIZEN TRIDONIC VS LIGHTING SOLUTIONS

LED | IP 66 | COB | 1-10 DIMMING | DALI | PHASE DIMMING | AC 85-265V 50/60Hz | 100 Lm/W | CRI >90 | UGR <19 | SDCM 2.0/3.0 | CIDET

IK08 | CE | ANTI GLARE | EYE COMFORT | -25°C - 55°C | ENERGY STAR | COMPLIANCE TM-21 | GLOWING WIRE TEST - 850° | UV | RoHS | COMPLIANCE | ECO

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that has recent technology will not alter the function of the product. Specification sheets found at www.pro-luce.com are the most recent versions and supercede all other printed or electronic versions.