OVANIA

OVANIA presenta un design avanzato e ad alte prestazioni per fari da esterno orientabili, progettato con ottiche di precisione per moderne applicazioni paesaggistiche, da giardino e di facciata. Offre un puntamento direzionale versatile, un'eccezionale resistenza agli agenti atmosferici e prestazioni affidabili, garantendo un'illuminazione d'accento potente e un comfort visivo superiore per ambienti esterni moderni.


OVANIA features an advanced, high-performance adjustable outdoor architectural spotlight design engineered with precision optics for contemporary landscape, garden, and facade applications. It offers versatile directional aiming, exceptional weather resistance, and dependable performance—delivering powerful accent lighting with superior visual comfort for modern outdoor environments.



Description


Housing - High-grade aluminum construction with Tiger powder spraying surface treatment. Designed for outdoor adjustable installation
Diffuser - High-performance optical lens with precise beam control.
Reflector - Precision beam control (15°, 25°, 36°, 50°).
LED - Sustainable energy savings enabled by advanced LED technology (Efficiency: 100 Lm/W, UGR<19).
L80 / B10 @ 50,000 h (LM-80 / TM-21)
L70 / B15 @ 100,000 h (projected lifetime under typical conditions)
Failure rate: F10 @ 50,000 h, Ta -20°C ~ 50°C
Standards - Manufactured in accordance with tested as per PTPS IES 62722, Glowing Wire Test 850° ; IP66, IK08.


Model	Power	Illuminance	Size(mm)
OVANIA-36	36W	3600Lm	Ø136-Ø150-375mm (Ground anchor range:Ø150-Ø400)



- 6500 K
- 6000 K
- 5000 K
- 4000 K
- 3000 K
- 2700 K
- TUNABLE SMART

k





CREE SHARP SAMSUNG PHILIPS CITIZEN TRIDONIC VS LIGHTING SOLUTIONS

LED | IP66 IK08 | COB | 1-10 DIMMING | DALI | PHASE DIMMING | AC 85-265V 50/60Hz | 100 Lm/W | CRI >90 | UGR <19 | SDCM 2.0/3.0 | CIDET

Adjusting | CE | ANTI GLARE | EYE COMFORT | -25°C 55°C | COMPLIANCE TM-21 | GLOWING WIRE TEST - 850° | RoHS | ECO

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that has recent technology will not alter the function of the product. Specification sheets found at www.pro-luce.com are the most recent versions and supercede all other printed or electronic versions.