
SINO TL

SINO TL presenta un elegante anello frontale fisso da incasso o un anello frontale regolabile fisso da incasso, progettato per applicazioni architettoniche moderne. Realizzato con ottiche di precisione ad alte prestazioni, offre un controllo costante del posizionamento, un'illuminazione confortevole anti-abbagliamento e prestazioni affidabili, garantendo un profilo a soffitto continuo e un comfort visivo superiore per ambienti contemporanei.

SINO TL features a sleek, fixed embedded face ring or fixed embedded adjustable face ring engineered for modern architectural applications. Crafted with high-performance precision optics, it offers steady positioning control, comfortable anti-glare illumination, and reliable performance—delivering a seamless ceiling profile and superior visual comfort for contemporary environments.



Cutout Ø55mm




Description


Housing - Die-cast aluminium with anti-corrosion powder coating (matte white, matte black, gun black, bright silver). Designed for recessed installation with an adjustable irradiation method.
Diffuser - Deep-recessed polycarbonate lens.
Reflector - Anodized aluminum with precision beam control (15°, 24°, 36°, 55°).
LED - Sustainable energy savings enabled by advanced LED technology (Efficiency: 100 Lm/W, UGR<19).
L80 / B10 @ 50,000 h (LM-80 / TM-21)
L70 / B15 @ 100,000 h (projected lifetime under typical conditions)
Failure rate: F10 @ 50,000 h, Ta -20°C ~ 50°C
Standards - Manufactured in accordance with tested as per PTPS IES 62722, Glowing Wire Test 850°

Model	Power	Illuminance	Size(mm)	Cutout
SINO TL 55	7W	700Lm	Ø60-76mm	Ø55mm
SINO TL 75	12W	1200Lm	Ø82-88mm	Ø75mm
SINO TL 95	24W	2400Lm	Ø110-125mm	Ø95mm

- 6500 K
- 6000 K
- 5000 K
- 4000 K
- 3000 K
- 2700 K
- TUNABLE SMART

k





CREE SHARP SAMSUNG PHILIPS CITIZEN TRIDONIC VS LIGHTING SOLUTIONS

LED | IP20 | COB | 1-10 DIMMING | DALI | PHASE DIMMING | AC 85-265V 50/60Hz | 100 Lm/W | CRI >90 | UGR <19 | SDCM 2.0/3.0 | CIDET

Adjusting | CE | ANTI GLARE | EYE COMFORT | -25°C 55°C | COMPLIANCE TM-21 | GLOWING WIRE TEST - 850° | RoHS | ECO

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that has recent technology will not alter the function of the product. Specification sheets found at www.pro-luce.com are the most recent versions and supercede all other printed or electronic versions.